

MOBIUZ

Imagine a New Reality

BenQ MOBIUZ Gaming Monitor EX480UZ

Enjoy the ultimate audiovisual gaming experience and follow an adventurous road that BenQ MOBIUZ leads you to with total immersion. EX480UZ, the 48" UHD OLED gaming monitor built for gaming but is perfect for every usage, provides smooth game play via superfast 0.1ms GTG, 120Hz, and AMD FreeSync Premium, and elevates sight and sound enjoyment via BenQ-exclusive HDRi and treVolo technology.



Fast Responses without Tears and Blurs

MOBIUZ gaming monitors deliver the quality astute gamers demand. With the fast refresh rate at 120Hz, 0.1ms GTG and AMD FreeSync Premium, no screen blurring, stuttering, or tearing gives a smooth visual experience, increasing gamers' absorption in the gameplay.



True Color Reproduction with Ultra Black

The OLED display reproduces true colors by delivering perfect hues, saturation, and contrast while expressing perfect black. Vivid colors are presented as EX480UZ covers 98% DCI-P3 color gamut with Delta E <= 2




Immersion Beyond Imagination

BenQ's proprietary HDRi auto-optimizes image color detail and clarity for vibrant images. It improves contrast by saturating colors and by auto-adapting to ambient light to make a unique MOBIUZ gaming experience.



Enchanting Sound Performance

BenQ's treVolo experts designed a player-specific surround sound field and special sound mode for different game types which configures high-middle and bass settings.



Additional Powerful Subwoofer

Catch every low-pitched bass note like the rumbling of gunfire. The 2.1 channel amplifier's 10W subwoofer delivers vibrant bass



Comfortable Extended Gameplay

BenQ proprietary Eye-Care technology is easy on your eyes so you experience greater comfort during long gaming sessions



BenQ MOBIUZ Gaming Monitor EX480UZ

| Product Color | Beng Mobioz Gaming Monitor | | |
|---|---|---|--|
| CD Size (Inch) 47.53 A55 A5 | Product Color | Metallic Gray | |
| Aspect Ratio 16:08 Display Area(mm) 18:22,x3518 Plood Pitch (mm) 02:74 Brightness (typ) 458 Native Contrast (typ.) 13500001 Plouel Type OLEB Viewing Angle (L/R-U/p) (CR) = ID) 178/178 Response time Units (StG) Display Cotors 10.73 Billon colors Color demut Directable Net Weight (kg) 19.3 Process Weight (kg) 49.8 Process Weight (kg) 19.4 Process Weight (kg) 19.4 | | nel OLED | |
| Besout/On (max) 3440-2160 Display Area (mm) 1052-22581 Pivel Pirch (mm) 450 Display Area (mm) 1052-2581 Display Colors 1550001 Display Colors 1550001 Display Colors 15781678 Begonse lime 15781678 Display Colors 10781678 | LCD Size (inch) | 47.53 | |
| Display Area (mm) 0.0274 1000 | Aspect Ratio | 16:09 | |
| Rick Pick | Resolution (max.) | 3840x2160 | |
| Rick Pick | Display Area(mm) | 1052.2x591.8 | |
| Project Province Province | | 0.274 | |
| Notive Contract (typ.) 3350004 Prone! Type OLED Viewing Angle (I/R,u/Ib) (CRP+ID) 175/178 Response time 0.01ms (crtc) Display colors 10.75 fillon colors Color Gamut DCI P3 98% Dimensions (H x W x D mm) 700x1068.5x267.6 Net weight (kg) 19.3 Type (Like) 19.3 Yes AMA Yes AMA Yes Flicker-free Technology 10.8 Game+libris / CinemaHDRi / FPS / RPG / Racing game / sR08 / M-book / Display P3/ Custom Brightness Intelligence Plus (B.I.+) Yes Color Mode 110R / Game+libris / CinemaHDRi / FPS / RPG / Racing game / sR08 / M-book / Display P3/ Custom Brightness Intelligence Plus (B.I.+) Yes Color Widerines Yes Poper mode Yes Low Rule Light Yes Low Rule Light Yes Slock Avoilise Yes Vibrance Yes Slock Avoilise Yes William Auguster Yes | | | |
| Pame Type Viewing Angle (Lift, RtJI/D) (CR2=10) T78/178 | | | |
| Viewing Angle (U/R.U/D) (CR0 = 10) Response time 0.1ms (R04) Display Colors 1.07 Billon colors 1.07 B | 1111 | | |
| Response time Dinns (GIG) 107 Billon colors 107 Billon co | | | |
| Display Colors 1.07 Billion colors Color Gamult Dimension - Weight Dimensions (Hxw x D mm) 700x10 68.5x267.6 Net Weight (kg) 19.3 Gross Weight (kg) 24.5 Type (Life State Sta | | | |
| Dimensions (H x W x D mm) 700x168.5x267.6 Net Weight (kg) 19.3 Gross Weight (kg) 24.5 Video Format Support 76.6 Video Format Suppor | | | |
| Dimensions (H x W x D mm) | | | |
| Dimensions (H x W x D mm) 700x10685x267.6 Net Weight (kg) 19.3 Cross Weight (kg) 24.5 Video Format Support Video Format Support Yes MAM Yes Elicker-free Technology Yes Color Mode HDR / GameHDRI / CinemaHDRI / FPS / RPG / Racing game / sRG8 / M-book / Display P3/ Custom Brightness Intelligence Plus (B.I.+) Yes Color Weakness Yes Popper mode Yes Low Blue Light Yes Usb I Juner Yes Color Vibrance Yes Black eQualizer Yes VESA Wall Mounting 2000 x 2000 x 200 Visit (down/up) -2° - 15° Wivel NA High adjustment Yes Locker Yes HDR Mode Yes Power cord (18m), HDM12 cloble (18m), P1 to Dr cable (18m), Remote Control USB-C Power cord (18m), HDM12 cloble (18m), Remote Control Popp I I I I I I I I I I I I I I I I I I | | | |
| Net Weight (kg) 19.3 Gross Weight (kg) 24.5 Video Format Support Yes AMA Yes Elicker-free Technology Pos Color Mode HDR / CameHDRI / CinemaHDRI / FPS / RPO / Racing game / sROB / M-book / Display P3/ Custom Brightness Intelligence Plus (BJ.+) Yes Color Weakness Yes ePaper mode Yes Low Blue Light Yes Low Blue Light Yes Use Well Light Yes Black eQualizer Yes VESA Wall Mounting 200 x 200 Till (down/up) -2° - 15° Swivel NA HIGH Mode Yes Other Accessories Power cord (18m), HDM1 21 cable (18m), DP to DP cable (18m), BC cable (18m), BC cable (18m), BC cable (18m), Remote Control Speaker 21 channel (5mx2 + 10W woofer) HDM 21 channel (5mx2 + 10W woofer) Speaker 21 channel (5mx2 + 10W woofer) HDM 21 channel (5mx2 + 10W woofer) SPDIF X1 Headphons Jack X1 | | | |
| Special Spe | | 700x1068.5x267.6 | |
| Video Format Support Yes AMA Yes Flicker-free Technology Yes Color Mode HDR / GameHDR / CinemothDR / FPS / RPG / Racing game / sRGB / M-book / Display P3 / Custom Brightness Intelligence Plus (B.I.+) Yes Color Weakness Yes ePager mode Yes Low Blue Light Yes Low Blue Light Yes Usual Light Tuner Yes Color Vibrance Yes Black eQualizer Yes VESA Wall Mounting 200 x 200 Till (aown/up) -2°-15° Swivel NA High adjustment NA K Locker Yes HDR Mode Yes Other Accessories Power cord (1.8m), HDMI 2.1 cable (1.8m), DP to DP cable (1.8m), USB-C cable (1m), USB3.1 Genl upstream cable (1.8m), Remote Control VSPOIL X1 USB-C X1 USB-C X1 Power Delivery 90W, DisplayPort Alt Mode, Data) X1 SPDIF X1 Headphone Jack X1 | | 19.3 | |
| Video Format Support Yes AMA Yes Flicker-free Technology Yes Color Mode HDIR / GameHDRi / CinemaHDRi / FPS / RPG / Racing game / sRGB / M-book / Display P3/ Custom Brightness Intelligence Plus (81.+) Yes Color Weakness Yes ePoper mode Yes Low Blue Light Yes Light Tuner Yes Color Vibrance Yes Black eQualizer Yes VESA Wall Mounting 2000 x 200 Till (down/up) -2° - 15° Swivel NA HIGH Accessories Power cord (18m), PDM L21 cable (18m), PP to DP cable (18m), PR to DP cable (| Gross Weight (kg) | 24.5 | |
| AMA Yes Flicker-free Technology Yes Color Mode HIDR / GameHDRI / CinemaHDRI / FPS / RPC / Racing game / sRGB / M-book / Display P3/ Custom Brightness Intelligence Plus (B.I.+) Yes Color Weakness Yes Peoper mode Yes Low Blue Light Yes Light Tuner Yes Color Vibrance Yes Black eQualizer Yes VESA Wall Mounting 200 x 2000 Till (down/up) -2º - 15º Swivel NA K Locker Yes HDR Mode Power cord (1.8m), HDMI 21 cable (1.8m), DP to DP cable (1.8m), Remote Control Usb-C cable (Im), USB31 Gen1 upstream cable (1.8m), Remote Control USB-C Y21 x 2 Spacker 21 channel (5Wx2 + 10W woofer) HDM Y21 x 2 PDI Input X1 HDK Mode Y21 x 2 PDI Input X1 Leadphone Jack X1 USB-C X1 Headphone Jack X1 USB X2 (Downstream) X1< | Special feature | | |
| Flicker-free Technology | Video Format Support | Yes | |
| HDR GameHDRi CinemaHDRi FPS RPG Racing game sRGB M-book Display P3 Custom Prightness Intelligence Plus (B.I.+) | AMA | Yes | |
| HDR GameHDRi CinemaHDRi FPS RPG Racing game sRGB M-book Display P3 Custom Prightness Intelligence Plus (B.I.+) | Flicker-free Technology | Yes | |
| Racing game sR6B M-book Display P3 Custom | | HDR / GameHDRi / CinemaHDRi / FPS / RPG / | |
| Brightness Intelligence Plus (B.I.+) Yes Color Weakness Yes ePoper mode Yes Low Blue Light Yes Light Tuner Yes Color Vibrance Yes Black eQualizer Yes VESA Wall Mounting 200 x 200 Tilk (down/up) -2*-15* Swivel NA High adjustment NA K Locker Yes HDR Mode Yes Other Accessories Power cord (1.8m), HDMI 2.1 cable (1.8m), DP to DP cable (1.8m), USB-C cable (1m), USB3.1 Gen1 upstream cable (1.8m), Remote Control VESP-C 2.1 channel (5wx2 + 10w woofer) HDMI y2.1 x 2 DP Input y1.4 x 1 USB-C x1 (PowerDelivery 90W, DisplayPort Alt Mode, Data) x1 SPDIF x1 Heddphone Jack x1 USB 32 (Downstream) x2 USB Type B (Upstream) x2 Ves Built- Power Consumption (Power saving mode) 0.5W Power Consumption (Power savi | Color Mode | | |
| Color Weakness Yes ePaper mode Yes Low Blue Light Yes Light Tuner Yes Color Vibrance Yes Black eQualizer Yes VESA Wall Mounting 200 x | | | |
| PePaper mode | | Yes | |
| Light Tuner | | Yes | |
| Light Tuner Yes Color Vibrance Yes Black eQualizer Yes VESA Wall Mounting 200 x 200 Tilk (down/up) -2° - 15° Swivel NA High adjustment NA K Locker Yes HDR Mode Yes Other Accessories Power cord (1.8m), HDMI 2.1 cable (1.8m), DP to DP cable (1.8m), usb-c cable (1m), USB3.1 Gen1 upstream cable (1.8m), Remote Control HDM V2.1 x 2 DP Input V2.1 x 2 DP Input V1.4 x 1 USB-C x 1 (PowerDelivery 90W, DisplayPort Alt Mode, Data) X 1 SPDIF X 1 Headphone Jack X 1 USB 3.2 (Downstream) X 2 USB Type B (Upstream) X 2 USB Type B (Upstream) Built-in Power Supply (90-264 AC) Built-in Power Consumption (Off mode) 0.5W Power Consumption (Off mode) 0.5W Power Consumption (Off mode) 0.05W Power Consumption (Off mode) 0.05W | ePaper mode | Yes | |
| Color Vibrance Yes Black eQualizer Yes VESA Wall Mounting 200 x 200 Till (down/up) -2° - 15° Swivel NA High adjustment NA K Locker Yes HDR Mode Yes Other Accessories Power cord (1.8m), HDM12.1 cable (1.8m), DP to DP cable (1.8m), BP to DP cable (1. | Low Blue Light | Yes | |
| Name | Light Tuner | Yes | |
| VESA Wall Mounting 200 x 200 Tilt (down/up) -2° ~ 15° Swivel NA High adjustment NA K Locker Yes HDR Mode Yes Other Accessories Power cord (1.8m), HDMI 2.1 cable (1.8m), DP to DP cable (1.8m), usbar. Jean cable (1.8m), Remote Control Usbar-Cable (Im), Usba. Jean upstream cable (1.8m), Remote Control Usbar-Cable (Im), Usba. Jean upstream cable (1.8m), Remote Control Usbar-Cable (Im), Usba. Jean upstream cable (1.8m), Remote Control Usbar-Cable (Im), Usba. Jean upstream cable (1.8m), Remote Control Usbar-Cable (Im), Usba. Jean upstream cable (1.8m), Remote Control Usbar-Cable (Im), Usba. Jean upstream cable (1.8m), Remote Control Usbar-Cable (Im), Usba. Jean upstream cable (1.8m), Proto DP cable (1.8m), Remote Control Usbar-Cable (Im), Usba. Jean upstream cable (1.8m), DP to DP cable (1.8m), Remote Control Usbar-Cable (Im), Usba. Jean upstream cable (1.8m), DP to DP cable (1.8m), Remote Control Usbar-Cable (Im), Usba. Jean upstream cable (1.8m), DP to DP cable (1.8m), Proto DP cable (1. | Color Vibrance | Yes | |
| Till (down/up) -2° - 15° Swivel NA High adjustment NA K Locker Yes HDR Mode Yes Other Accessories Power cord (18m), HDMI 2.1 cable (1.8m), DP to DP cable (1.8m), USB-C cable (1m), USB3.1 Gen1 upstream cable (1.8m), Remote Control USB-C HDMI V2.1 x 2 DP Input V1.4 x 1 USB-C X1 (PowerDelivery 90W, DisplayPort Alt Mode, Data) X1 SPDIF X1 Headphone Jack X1 USB 3.2 (Downstream) X2 USB 1/2 pp B (Upstream) X1 USB 3.2 (Downstream) X2 USB Type B (Upstream) X1 Power Supply (90-264 AC) Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.3W MTEF (hr, exclude lamp) Certification TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | Black eQualizer | Yes | |
| Till (down/up) -2° - 15° Swivel NA High adjustment NA K Locker Yes HDR Mode Yes Other Accessories Power cord (18m), HDMI 2.1 cable (1.8m), DP to DP cable (1.8m), USB-C cable (1m), USB3.1 Gen1 upstream cable (1.8m), Remote Control USB-C HDMI V2.1 x 2 DP Input V1.4 x 1 USB-C X1 (PowerDelivery 90W, DisplayPort Alt Mode, Data) X1 SPDIF X1 Headphone Jack X1 USB 3.2 (Downstream) X2 USB 1/2 pp B (Upstream) X1 USB 3.2 (Downstream) X2 USB Type B (Upstream) X1 Power Supply (90-264 AC) Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.3W MTEF (hr, exclude lamp) Certification TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | VESA Wall Mounting | 200 x 200 | |
| Swivel NA High adjustment NA K Locker Yes HDR Mode Yes Other Accessories Power cord (1.8m), HDMI 2.1 cable (1.8m), DP to DP cable (1.8m), Remote Control USB-C cable (1m), USB3.1 Genil upstream cable (1.8m), Remote Control USB-C cable (1m), USB3.1 Genil upstream cable (1.8m), Remote Control USB-C cable (1m), USB3.1 Genil upstream cable (1.8m), Remote Control USB-C v2.1 x 2 PDINDI V2.1 x 2 USB-C v1, x 1 V1.4 x 1 USB-C (PowerDelivery 90W, DisplayPort Alt Mode, Data) x 1 SPDIF x 1 Headphone Jack x 1 USB 3.2 (Downstream) x 2 USB Type B (Upstream) x 2 USB Type B (Upstream) x 2 Power Supply (90-264 AC) Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.5W MTIBF (hr, exclude lamp) 600000 MTIBF (hr, exclude lamp) TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | | | |
| High adjustment NA K Locker Yes HDR Mode Yes Other Accessories Power cord (1.8m), HDMI 2.1 cable (1.8m), DP to DP cable (1.8m), USB-C cable (1m), USB3.1 Gen1 upstream cable (1.8m), Remote Control Job Speaker 2.1 channel (5Wx2 + 10W woofer) HDMI v2.1 x 2 DP Input v2.1 x 2 USB-C x1 (PowerDelivery 90W, DisplayPort Alt Mode, Data) x1 SPDIF x1 Headphone Jack x1 USB 3.2 (Downstream) x2 USB Type B (Upstream) x2 Power Supply (90-264 AC) Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.5W MTBF (hr, exclude lamp) 0.5W MTBF (hr, exclude lamp) TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | | | |
| K Locker Yes HDR Mode Yes Other Accessories Power cord (1.8m), HDMI 2.1 cable (1.8m), DP to DP cable (1.8m), usbs.1 Gen1 upstream cable (1.8m), Remote Control Joseaker HDMI V2.1 x 2 DP Input V2.1 x 2 USB-C X1 (PowerDelivery 90W, DisplayPort Alt Mode, Data) X1 SPDIF X1 Headphone Jack X1 USB 3.2 (Downstream) X2 USB Type B (Upstream) X1 Power Supply (90-264 AC) Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.5W MTBF (hr, exclude lamp) 60000 TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible TUV Flicker-free / TUV Low Blue Light | | | |
| HDR Mode Yes Other Accessories Power cord (1.8m), HDMI 2.1 cable (1.8m), DP to DP cable (1.8m), USB-C cable (1m), USB3.1 Gen1 upstream cable (1.8m), Remote Control Speaker 2.1 channel (5Wx2 + 10W woofer) HDMI v2.1 x 2 DP Input v1.4 x 1 USB-C x 1 (PowerDelivery 90W, DisplayPort Alt Mode, Data) x 1 SPDIF x 1 Headphone Jack x 1 USB 3.2 (Downstream) x 2 USB 7.2 (Downstream) x 2 USB Type B (Upstream) Built-in Power Supply (90-264 AC) Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.3W MTBF (hr, exclude lamp) 600000 TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | 3 . | | |
| Other Accessories Power cord (1.8m), HDMI 2.1 cable (1.8m), DP to DP cable (1.8m), USB-C cable (1m), USB3.1 Gen1 upstream cable (1.8m), Remote Control USB-C cable (1m), USB3.1 Gen1 upstream cable (1.8m), Remote Control VIO Speaker 2.1 channel (5Wx2 + 10W woofer) HDMI v2.1 x 2 DP Input v1.4 x 1 USB-C (PowerDelivery 90W, DisplayPort Alt Mode, Data) x 1 SPDIF x 1 Headphone Jack x 1 USB 3.2 (Downstream) x 2 USB Type B (Upstream) x 2 Power Supply (90~264 AC) Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.3W MTBF (hr, exclude lamp) 60000 TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible | | | |
| USB-C cable (Im), USB3.I Gen1 upstream cable (I.8m), Remote Control I/O Speaker | TIDIK MOGE | | |
| Speaker 2.1 channel (5Wx2 + 10W woofer) HDMI v2.1 x 2 DP Input v1.4 x 1 USB-C x 1 (PowerDelivery 90W, DisplayPort Alt Mode, Data) x 1 SPDIF x 1 Headphone Jack x 1 USB 3.2 (Downstream) x 2 USB Type B (Upstream) x 1 Power Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.3W MTBF (hr, exclude lamp) 600000 Certification TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | Other Accessories | | |
| Speaker 2.1 channel (5Wx2 + 10W woofer) HDMI V2.1 x 2 DP Input v1.4 x 1 USB-C (PowerDelivery 90W, DisplayPort Alt Mode, Data) x 1 SPDIF x 1 Headphone Jack x 1 USB 3.2 (Downstream) x 2 USB Type B (Upstream) x 1 Power Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.3W MTBF (hr, exclude lamp) 60000 Certification TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | | | |
| HDMI v2.1 x 2 DP Input v1.4 x 1 USB-C (PowerDelivery 90W, DisplayPort Alt Mode, Data) x 1 SPDIF x 1 Headphone Jack x 1 USB 3.2 (Downstream) x 2 USB Type B (Upstream) x 1 Power Power Supply (90~264 AC) Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.3W MTBF (hr, exclude lamp) 60000 Certification TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | | | |
| DP Input v1.4 x 1 USB-C (PowerDelivery 90W, DisplayPort Alt Mode, Data) x 1 SPDIF x 1 Headphone Jack x 1 USB 3.2 (Downstream) x 2 USB Type B (Upstream) x 1 Power Power Supply (90~264 AC) Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.3W MTBF (hr, exclude lamp) 60000 Certification TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | | | |
| USB-C (PowerDelivery 90W, DisplayPort Alt Mode, Data) SPDIF K 1 Headphone Jack USB 3.2 (Downstream) USB 3.2 (Downstream) V2 USB Type B (Upstream) Power Power Supply (90~264 AC) Power Supply (90~264 AC) Power Consumption (Power saving mode) Power Consumption (Off mode) MTBF (hr, exclude lamp) Certification TUV Certificate Mac Compatible X 1 X 1 X 1 X 1 X 1 X 1 X 2 X 2 | | | |
| (PowerDelivery 90W, DisplayPort Alt Mode, Data) SPDIF | DP Input | vl.4 x l | |
| (PowerDelivery 90W, DisplayPort Alt Mode, Data) SPDIF | USB-C | x1 | |
| Headphone Jack USB 3.2 (Downstream) USB Type B (Upstream) Power Power Supply (90~264 AC) Power Consumption (Power saving mode) Power Consumption (Off mode) MTBF (hr, exclude lamp) Certification TUV Certificate Mac Compatible X 1 X 2 X 1 X 2 X 1 X 1 X 2 X 1 X 1 | (PowerDelivery 90W, DisplayPort Alt Mode, Data) | | |
| USB 3.2 (Downstream) x 2 USB Type B (Upstream) x 1 Power Power Supply (90~264 AC) Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.3W MTBF (hr, exclude lamp) 60000 Certification TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | SPDIF | x 1 | |
| USB 3.2 (Downstream) x 2 USB Type B (Upstream) x 1 Power Power Supply (90~264 AC) Built-in Power Consumption (Power saving mode) 0.5W Power Consumption (Off mode) 0.3W MTBF (hr, exclude lamp) 60000 Certification TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | Headphone Jack | x1 | |
| USB Type B (Upstream) Power Power Supply (90~264 AC) Power Consumption (Power saving mode) Power Consumption (Off mode) MTBF (hr, exclude lamp) Certification TUV Certificate Mac Compatible X1 Built-in 0.5W 0.5W 0.3W 60000 TUV Flicker-free / TUV Low Blue Light Yes | | x 2 | |
| Power Supply (90~264 AC) Power Supply (90~264 AC) Power Consumption (Power saving mode) Power Consumption (Off mode) MTBF (hr, exclude lamp) Certification TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | | | |
| Power Supply (90~264 AC) Power Consumption (Power saving mode) Power Consumption (Off mode) MTBF (hr, exclude lamp) Certification TUV Certificate Mac Compatible Built-in 0.5W 0.3W 60000 TUV Flicker-free / TUV Low Blue Light Yes | | | |
| Power Consumption (Power saving mode) Power Consumption (Off mode) MTBF (hr, exclude lamp) Certification TUV Certificate Mac Compatible 0.5W 0.3W 60000 TUV Flicker-free / TUV Low Blue Light Yes | | | |
| Power Consumption (Off mode) MTBF (hr, exclude lamp) Certification TUV Certificate Mac Compatible 0.3W 60000 TUV Flicker-free / TUV Low Blue Light Yes | | | |
| MTBF (hr, exclude lamp) 60000 Certification TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | | | |
| TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | | | |
| TUV Certificate TUV Flicker-free / TUV Low Blue Light Mac Compatible Yes | | | |
| Mac Compatible Yes | | | |
| | | | |
| Windows® Compatible Windows® 11,10 | | | |
| | Windows® Compatible | Windows® 11,10 | |

^e 2022 BenQ Corp. Specification may vary by region, please visit your local stores for details. Actual product's features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively. Doc.: LCD_EX480UZ_DS_EN_0729

