Benq

TZY61

InstaShare Button Solution





4K Wireless Casting

Wirelessly cast lesson materials in stunning 4K quality to BenQ displays. The InstaShare Button works seamlessly with Windows laptops, MacBook®, and Chromebooks for effortless, one-click sharing.

* MacBook* is a trademark of Apple Inc.



USB-C All-in-One Connectivity

Enjoy a true plug-and-play experience with a single USB-C cable. It casts, powers, and enables touchback, eliminating the mess of multiple cables.



Multi-Device Collaboration

View up to 9 devices side-by-side using InstaShare 2. With touchback support, teachers can control any connected device directly from the BenQ Board.



Industry-Leading Connection Quality

Enjoy smooth classes without interruptions. Equipped with IEEE 802.11ac Wave 2 Wi-Fi, the InstaShare Button ensures fast, stable, and reliable screen sharing across the classroom.



Organised classrooms with InstaShare Dock

Keep your teaching space tidy and clutter-free. The InstaShare Dock stores InstaShare Buttons, pens, and remote controls neatly in one place.

Colour Silver			
TX button input resolution Audio rate Wi-Fi standard Authentication protocol Wireless security (encryption) Wireless coverage reach Cable Power supply Power consumption Dimension (W x H x D) Temperature range Humidity range Conpatibility Colour InstaShare Dock Product material Cable environment (1080P60 / 4K30P) Up to 4K30P Stereo, radio quality 16bits 48KHz Wieless 6SeHz, 2T2R MIMO Wi-Fi standard Wi-Fi standard Wi-Fi standard Wi-Fi standard WHA2/3 Personal / WPA2 Enterprise, support AES-256 Max. 15 m (between the button and the display) Cable USB Type-C Power supply DC 5V±10%, minimum 0.9A Max 4.5W full loading For mm x 67 mm x 23.2 mm Operating: 0°C to +40°C Storage: -10°C to +60°C Operating: 10% to 80% relative humidity storage: 5% to 90% relative humidity (non condensing) Compatibility RP03, RP03A, RM03, RM03A, VC01A, RP04 RM04, RE04 Product material PC-ABS, aluminium alloy 6063,	InstaShare Button	Colour	Silver
resolution Audio rate Stereo, radio quality 16bits 48KHz Wi-Fi standard Authentication protocol Wireless security (encryption) Wireless coverage reach Cable Power supply Power consumption Dimension (W x H x D) Temperature range Humidity range Compatibility Compatibility Color Power black Color RP03, RP03A, RM03, RM03A, VC01A, RP04 RM04, RE04 Color Wi-Fi standard WPA2/3 Personal / WPA2 Enterprise, support AES-256 Weight (net) WPA2/3 Personal / WPA2 Enterprise, support AES-256 Wax. 15 m (between the button and the display) Max. 15 m (between the button and the display) Coble USB Type-C Power supply DC 5V±10%, minimum 0.9A Poperating: 0°C to +40°C Storage: -10°C to +60°C Operating: 10% to 80% relative humidity (non condensing) RP03, RP03A, RM03, RM03A, VC01A, RP04 RM04, RE04 Colour Black Weight (net) Dimension (W x H x D) InstaShare Button loading quantity PC-ABS, aluminium alloy 6063,			
Wi-Fi standard Authentication protocol Wireless security (encryption) Wireless coverage reach (x 2) Wireless coverage reach (x 2) Wireless coverage reach (x 2) Wireless coverage reach (x 4) Cable USB Type-C Power supply DC 5V±10%, minimum 0.9A Power consumption Dimension (W x H x D) Temperature range Wireless coverage reach (x 2) Operating: 0°C to +40°C Storage: -10°C to +60°C Humidity range Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity Storage: 5% to 90% relative humidity (non condensing) Compatibility RP03, RP03A, RM03, RM03A, VC01A, RP04 RM04, RE04 Veight (net) Dimension (W x H x D) InstaShare Dock Product material PC-ABS, aluminium alloy 6063,			Up to 4K30P
TWY31 InstaShare Button (x 2) Wireless scurity (encryption) Wireless coverage reach (x 2) Wireless coverage reach Cable USB Type-C Power supply DC 5V±10%, minimum 0.9A Power consumption Dimension (W x H x D) Temperature range Humidity range Compatibility Compatibility Colour Wir-Fi standard Wir-Fi standard Wir-Fi standard Wir-Fi standard Wir-Fi standard WPA2/3 Personal / WPA2 Enterprise, support AES-256 Max. 15 m (between the button and the display) Cable USB Type-C Power supply DC 5V±10%, minimum 0.9A Porerating: 0°C to +40°C Storage: -10°C to +40°C Storage: -10°C to +60°C Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity (non condensing) RP03, RP03A, RM03, RM03A, VC01A, RP04 RM04, RE04 Weight (net) Black Weight (net) 366g Dimension (W x H x D) InstaShare Dock Product material PC-ABS, aluminium alloy 6063,		Audio rate	Stereo, radio quality 16bits 48KHz
TWY31 InstaShare Button (x 2) Wireless security (encryption) Max 4.5F m (between the button and the display) Cable USB Type-C Power supply DC 5V±10%, minimum 0.9A Power consumption Max 4.5W full loading 67 mm x 67 mm x 23.2 mm Operating: 0°C to +40°C Storage: -10°C to +60°C Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity (non condensing) Compatibility RP03, RP03A, RM03, RM03A, VC01A, RP04 RM04, RE04 Colour Black Weight (net) 366g Dimension (W x H x D) InstaShare Button loading quantity PC-ABS, aluminium alloy 6063,		Wi-Fi standard	IEEE 802.11ac 5GHz, 2T2R MIMO
TWY31 InstaShare Button (x 2) Wireless coverage reach Cable USB Type-C Power supply Power consumption Dimension (W x H x D) Temperature range Compatibility Compatibility Colour Black Weight (net) Dimension (W x H x D) Dimension (W x H x D) Power domain and the display) Max 1.5 m (between the button and the display) Max 1.5 m (between the button and the display) DC 5V±10%, minimum 0.9A Max 4.5W full loading For mm x 67 mm x 23.2 mm Operating: 0°C to +40°C Storage: -10°C to +60°C Operating: 10% to 80% relative humidity (non condensing) RP03, RP03A, RM03, RM03A, VC01A, RP04 RM04, RE04 Power consumption Max 4.5W full loading Operating: 0°C to +40°C Storage: -10°C to +60°C Operating: 10% to 80% relative humidity (non condensing) Dimension (W x H x D) Dimension (W x H x D) Dimension (W x H x D) Product material PC-ABS, aluminium alloy 6063,			Wi-Fi standard
InstaShare Button (x 2) Cable Dock Power supply Power consumption Dimension (W x H x D) Cappatibility Compatibility Colour Weight (net) Dimension (W x H x D) InstaShare Dock Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Max .15 m (between the button and the display) Possible Type -C Doc 5V±10%, minimum 0.9A Max .15 m (between the button and the display) Possible Type -C Doc 5V±10%, minimum 0.9A Max .15 m (between the button and the display in the display i			
Cable USB Type-C		•	` `
Power consumption Dimension (W x H x D) Temperature range Humidity range Compatibility Compatibility Colour Weight (net) Dimension (W x H x D) Dimension (W x H x D) Product material Max 4.5W full loading 67 mm x 67 mm x 23.2 mm Operating: 0°C to +40°C Storage: -10°C to +60°C Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity (non condensing) RP03, RP03A, RM03, RM03A, VC01A, RP04 RM04, RE04 Product material Max 4.5W full loading Operating: 0°C to +40°C Storage: -10°C to +40°C Storage: -10		Cable	USB Type-C
Dimension (W x H x D) Temperature range Operating: 0°C to +40°C Storage: -10°C to +60°C Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity (non condensing) Compatibility RP03, RP03A, RM03, RM03A, VC01A, RP04 RM04, RE04 Colour Black Weight (net) 366g Dimension (W x H x D) InstaShare Dock Product material PC-ABS, aluminium alloy 6063,		Power supply	DC 5V±10%, minimum 0.9A
Temperature range Operating: 0°C to +40°C Storage: -10°C to +60°C Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity (non condensing) RP03, RP03A, RM03A, RM03A, VC01A, RP04 RM04, RE04 Colour Black Weight (net) 366g Dimension (W x H x D) InstaShare Dock Product material Operating: 0°C to +40°C Storage: -10°C to +60°C Operating: 10% to 80% relative humidity (non condensing) RP03, RP03A, RM03A, RM03A, VC01A, RP04 RM04, RE04 POS Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity (non condensing) RP03, RP03A, RM03A, RM03A, VC01A, RP04 RM04, RE04 POS Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity (non condensing) RP03, RP03A, RM03A, RM03A, VC01A, RP04 RM04, RE04 POS Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity (non condensing) RP03, RP03A, RM03A, RM03A, VC01A, RP04 RM04, RE04 POS Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity (non condensing) RP03, RP03A, RM03A, RM03A, VC01A, RP04 RM04, RE04 POS Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity (non condensing) RP03, RP03A, RM03A, RM03A, VC01A, RP04 RM04, RE04 POS Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity (non condensing) RP03, RP03A, RM03A, RM03A, VC01A, RP04 RM04, RE04 POS Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity Stora		Power consumption	Max 4.5W full loading
Storage: -10°C to +60°C Humidity range Operating: 10% to 80% relative humidity Storage: 5% to 90% relative humidity (non condensing) Compatibility RP03, RP03A, RM03A, RM03A, VC01A, RP04 RM04, RE04 Colour Black Weight (net) 366g Dimension (W x H x D) InstaShare Dock Product material PC-ABS, aluminium alloy 6063,		Dimension (W x H x D)	67 mm x 67 mm x 23.2 mm
Humidity range Storage: 5% to 90% relative humidity (non condensing) RP03, RP03A, RM03, RM03A, VC01A, RP04 RM04, RE04 Colour Black Weight (net) 366g Dimension (W x H x D) InstaShare Dock Product material Storage: 5% to 90% relative humidity (non condensing) RP03, RP03A, RM03, RM03A, VC01A, RP04 RM04, RE04 Product material PC-ABS, aluminium alloy 6063,		Temperature range	
Colour Black Weight (net) 366g Dimension (W x H x D) 106 mm x 85 mm x 150 mm InstaShare Button loading quantity 4 pcs Product material PC-ABS, aluminium alloy 6063,		Humidity range	Storage: 5% to 90% relative humidity
InstaShare Dock Dimension (W x H x D) InstaShare Button loading quantity Product material PC-ABS, aluminium alloy 6063,		Compatibility	
InstaShare Dock Dimension (W x H x D) InstaShare Button loading quantity Product material PC-ABS, aluminium alloy 6063,			
InstaShare Dock Dimension (W x H x D) InstaShare Button loading quantity Product material PC-ABS, aluminium alloy 6063,		Colour	Black
Instashare Dock Instashare Button loading quantity 4 pcs Product material PC-ABS, aluminium alloy 6063,		Weight (net)	366g
loading quantity 4 pcs Product material PC-ABS, aluminium alloy 6063,		Dimension (W x H x D)	106 mm x 85 mm x 150 mm
Product material			4 pcs
		Product material	



