

BenQ

RE8605AC

Essential Series



EDLA-certified with Enhanced Security

The RE8605AC seamlessly integrates Google services with BenQ's reliable hardware and software, now powered by Android 16 for enhanced performance and long-term compatibility. Easily access Google/Microsoft tools and education apps via the Google Play Store and ensure data protection using secure login options, access controls, regular system updates, and built-in Google Play Protect and Safe Browsing.



Advanced Management Solutions (DMS & AMS)

The RE8605AC series features BenQ's cloud-based DMS and AMS, providing centralised control of displays and user accounts from a single dashboard. DMS simplifies device setup with quick onboarding, remote configuration, app management, firmware updates, and task automation, while offering real-time analytics and energy usage insights. AMS ensures secure, personalised access with single sign-on and integration with cloud storage platforms such as Google Drive, OneDrive, and Nextcloud, keeping user data separate and allowing customised settings for a consistent user experience.



Comfortable Viewing with Eye Care Technologies

The RE8605AC interactive display features a bright 500-nit anti-glare 4K screen for clear visibility in any classroom. Its 84W audio system with integrated subwoofers and an 8-microphone array with echo cancellation supports clear communication for hybrid learning. The germ-resistant screen helps promote healthier classrooms, while NFC enables quick and secure access. Built-in eye care technologies, including low blue light and a flicker-free screen, reduce eye strain for comfortable extended use.



Panel	Screen size		86"
	Resolution		UHD 3840 × 2160
	Brightness		500 nits
	Typical contrast ratio		5500:1
	Dynamic contrast ratio		50,000:1
	Viewing angle (H/V)		178°/178°
	Response time		6.5 ms
	Backlight life		50,000 hrs
	Panel surface		AG, Haze 25%
	Operating hours		18 hours / 7 days
System	Orientation		Landscape
	Memory Storage		8 GB 128 GB
	OS		Android 16.0 (EDLA)
	GPU		Arm Mali-G52 MC3
	CPU		Octa-Core (A72 × 4 + A53 × 4)
Power	NPU		6 TOPS
	Power supply		AC 100-240 V, 50/60 Hz
	Power consumption	Typical	115.2 W
		Standby	<0.5 W
	AC power switch		No
Touch	ENERGY STAR®		Yes
	Wake up		LAN / HDMI
	Technology		Precision IR
	Number of touch points		up to 50
	Interface		USB Type-B × 2
Glass	Thickness		3.2 mm
	Hardness		9H tempered
	AG coating		Yes
ClassroomCare® Technology	Eye care: flicker-free & low blue light		Yes (TÜV-certified)
	Air quality sensors & air ioniser		No
	Germ-resistant screen		Yes (certified by TÜV, SIAA & SGS)
Environment	Operating temperature		0°C ~ 40°C
	Operating humidity		20% ~ 80% RH non-condensing
Connectivity	Input		HDMI 2.0 × 3, Mic (3.5mm) × 1
	Output		HDMI 2.0 × 1, SPDIF (Optical) × 1, Earphone × 1
	USB		Type-A × 4 (3.0 × 3 / 2.0 × 1), Type-B × 2 (2.0), Type-C × 1 (3.0, 5-in-1: data, video, audio, touch, PD 65 W)
	RS-232 (in)		× 1
	RJ45 (LAN)		× 1 (Android: up to 1000 Mbps / OPS: up to 100 Mbps)
	Wireless connectivity		Optional WD02AT (Wi-Fi 6, Bluetooth 5.2)
	OPS slot (for slot-in PC)		× 1
Built-in peripherals	Speaker		12 W × 2
	Subwoofer		30 W × 2
	Microphones		8-mic array w/ echo cancellation, up to 12 m pickup range
	Camera with cover	Resolution	50MP 4K
		FOV	D 115°, H 101°, V 84.7°
		AI features	AI auto framing, AI auto voice tracking
Physical	NFC Sensor		Yes
	Dimensions (W × H × D)		1960.2 × 1191.2 × 100.5 mm
	Weight (product shipping)		56.5 kg 65.5 kg
	Bezel width (T B L R)		15.1 15.1 15.1 44.1 mm
	Wall mounting (VESA) (screw type/max length)		VESA 800 × 600 mm (4 × M8 × 25L), wall mount kit included
Accessories	Remote control		× 1
	Stylus		× 2 (PT06)
	Cables		HDMI (3 m) × 1, USB-B for touch (3 m) × 1

→ Specifications subject to change without notice.



ENERGY STAR®



El diseño energéticamente eficiente de las pantallas RE7505 cumple los estándares ENERGY STAR® y puede reducir el consumo de energía hasta un 70%.

Embalaje sostenible



Hemos reducido nuestra huella de transporte y logística aumentando la tasa de carga en un 60%.

Control de energía remoto



Reduce el consumo de energía innecesario con DMS apagando y encendiendo pantallas de forma remota y estableciendo programaciones.

SOFTWARE



EZWrite 6

Guarda lecciones en archivos de pizarra editables (IWB) con Cloud Whiteboarding. Google Classroom está integrado con EZWrite WEB.



InstaShare 2

Compartición inalámbrica de pantalla y transmisión desde cualquier dispositivo. Comparte varias pantallas simultáneamente con diferentes tipos de contenido.



X-Sign Broadcast

Sistema de comunicados con comunicación entre campus. Envía alertas visuales, avisos y vídeos a todos los dispositivos o a uno específico.



AMS

Sistema de gestión de cuentas para cargar y acceder de forma cómoda a tu cuenta y almacenamiento en la nube desde cualquier pantalla BenQ.



DMS

La solución de gestión de dispositivos supervisa de forma centralizada todas las pantallas para obtener información de estado en tiempo real, desplegar actualizaciones OTA y más.

TERMINALES DE ENTRADA Y SALIDA

KEYPAD BUTTONS



FRONT I/O



NFC SENSOR



LIGHT SENSOR IR SENSOR



TYPE-C 3.0



HDMI




TOUCH-USB



PUBLIC 3.0



SIDE I/O (LEFT)



PUBLIC 3.0



PUBLIC 2.0



TOUCH USB



HDMI OUT



HDMI 1



HDMI 2




LAN



EARPHONE

MIC-IN






RS-232



SPDIF

DIMENSIONES (MM)



Los términos y condiciones de la garantía pueden cambiar según el país de compra y las normativas locales.



www.benq.eu/es-es/education.html

© 2026 BenQ Corp. Las especificaciones pueden variar según la región; visita tus tiendas locales para más detalles. Las características y especificaciones reales del producto están sujetas a cambios sin previo aviso. Este material puede incluir nombres corporativos, marcas comerciales y logotipos de terceros que son propiedad de sus respectivos titulares.

BENQ