



Edit, manage, and customise content through the **X-Sign Content Management** Software by using the 150+ templates available.



Remotely manage all screens, and display different contents across various locations. Monitor real-time performance, and get instant notifications about displays' status.



The DEY21 can be wired to the network (LAN) or via Wi-Fi, through the **360° adjustable antenna** for a strong and stable signal.



SPECIFICATIONS		
System	Processor	Dual Cortex-A72 + Quad Cortex-A53
	Graphics	Mali-T864
	Memory	4G
	Storage	32G
	Platform	Android 7.1
I/O	HDMI out	xI (up to 4K@25Hz)
	USB	Type A (3.0 \times 1, 2.0 \times 3), Type C \times 1 (video/data)
	LAN (Gigabit Ethernet)	xl
	TF slot (Micro SD)	xl
	Line in & Line out (3.5mm jack)	xI (2 in I)
	Antenna	x2
Wireless Connection		WiFi 802.11 ac/b/g/n + BT4.1
Codec	Video	H.264/AVC, Base/Main/High/High10 profile@level 5.1;up to 3840x2160@ 30fps; H.265/ HEVC, Main/Main10 profile@level 5.1 High-tier:up to 3840x2160@ 60fps; VP9, profile 0, up to 3840x2160@ 60fps MPEG-1 up to 1080P @ 60fps; MPEG-2 SP@ML, MP@HL, up to 1080P @ 60fps; MPEG-4 SP@L0-3, ASP@L0-5, up to 1080P @ 60fps; VC-1, SP@ML, MP@HL, AP@L0-3, up to 1080P @ 60fps
	Image	BMP/PNG/JPG up to 3840x2160
Power (adaptor)		I2V DC in
Dimension (L x W x H)		28 mm × 128 mm × 30 mm
Environment	Operating temperture	-0°~45°
	Storage temperture	-20°~70°
Relative humidity		10%~95% (non-condensing)

[→] Specifications are subject to change without notice. For the most up to date information, please visit benq.eu/en-eu/business.



