Beno

RP7503

Pro Series













MeetingroomCare* protects users' health and vision: The certified germ-resistant **coating** is applied on the front ports, pens, remote controls, and screens. Plus, RP03 delivers optimal colour performance thanks to its low blue light feature, which makes it the world's first interactive display approved by Eyesafe®.



With the built-in air quality sensor and air ioniser, meeting rooms can both be monitored for pollutant particles and cleansed by negative ions that are released automatically or remotely via DMS.



With the **dedicated USB port** for cameras, RP03 Series allows remote participants to see every attendee in the meeting room during video conferencing.

Panel		Screen size		75"
Panel		Resolution		4K UHD 3840 × 2160
Panel		Brightness (typ.)		400 nits
Panel		Contrast ratio (typ.)		1200:1
Response time (G-t-G)				30,000 : 1
Backlight life (hrs)	Panel	Viewing angle (H/V)		178°
Panel surface		Response time (G-t-G)		8 ms
Operating hours		Backlight life (hrs)		50,000
Orientation System memory 8 GB		. ,		AG, Haze 25%
Platform solution Storage		Operating hours		18 hours / 7 days
Platform solution		Orientation		Landscape
Power supply		System memory		8 GB
Power Pow	Platform solution	Storage		64 GB
Power Power Consumption Typical (W/h) 90 90 90 90 90 90 90 9		os		Android 11
Power Consumption Typical (W/h) 90		Power supply		100-240 V 50/60 Hz
Power			Maximum (W/h)	461
Standby mode (W/h)			Typical (W/h)	90
Touch Wake up			Standby mode (W/h)	<0.5
Technology		AC power switch		Yes
Number of touch points 40 Interface		Wake up		LAN / HDMI / VGA / DP
Interface		Technology		Fine IR Plus
Tempered glass 3.2 mm Hardness 9H AG coating Yes Smart Eye-Care solution Flicker-free & Low blue light (TÜV & Eyesafe® certified) MeetingroomCare* Technology Air quality sensor CO2 - PM2 - PM1, Temperature & Humidity, Air ioniser Germ-resistant screen Yes (TÜV & SIAA certified) Operation temperature 0°C ~ 40°C Operating humidity 20% ~ 80% RH non-condensing Energy efficiency Energy Star 8.0 certified Output HDMI 2.0 x 1, Audio (3.5 mm) x 1 Output HDMI 2.0 x 1, Audio (3.5 mm) x 1 Output HDMI 2.0 x 1, Audio (3.5 mm) x 1 Output HDMI 2.0 x 1, Audio (3.5 mm) x 1 VSB Type A x 7 (2.0 x 2 / 3.2 Gen 1 x 5), Type B x 3 (3.0), Type C x 2 (3.0) RS232 x 1 RJ45 (LAN) x 2 (Android / OPS) up to 1000Mbps Remote controller x 1 Audio Array microphones x 8 Audio Dolby Audio Yes Array microphones x 8 Dimension (mm) Screen 1717.1 x 1065.3 x 121.3 mm Meight (kg) Gross weight 70 Bezel width (mm) 16.6 / 16.6 / 16.6 / 16.6 Wall mount kit Included OPS slot Yes NFC sensor Active Directory and Google Workspace Pen tray Yes		Number of touch points		40
Hardness AG coating Yes		Interface		USB Type B x 3
AG coating Yes	MeetingroomCare*	Tempered glass		3.2 mm
MeetingroomCare* Technology		Hardness		9H
Smart Eye-Care solution Eyesafe® certified		AG coating		Yes
Air quality sensor		Smart Eye-Care solution		
Departion temperature				
Environment Operating humidity Energy efficiency 20% ~ 80% RH non-condensing Energy efficiency Energy Star 8.0 certified Input VGA x 1, HDMI 2.0 x 3, DP 1.2a x 1, Audio (3.5 mm) x 1 Connectivity USB Type A x 7 (2.0 x 2 / 3.2 Gen 1 x 5), Type B x 3 (3.0), Type C x 2 (3.0) RS232 x 1 RS232 x 1 Ry45 (LAN) x 2 (Android / OPS) up to 10000Mbps Remote controller x 1 Built-in speaker 2 x 16 W / 1 x Subwoofer 16 W Dolby Audio Yes X8 Array microphones x 8 X8 Weight (kg) Screen 1717.1 x 1065.3 x 121.3 mm Weight (kg) To To Bezel width (mm) 16.6 / 16.6 / 16.6 / 16.6 Wall mounting (VESA) (screw type / max. length) 800 x 400 (4 x M8 x 25L) Wall mount kit Included OPS slot Yes NFC sensor Yes (supports single sign-on with Azure Active Directory and Google Workspace) Pen tray Yes		Germ-resistant screen		Yes (TÜV & SIAA certified)
Energy efficiency	Environment	Operation temperature		0°C ~ 40°C
Input		Operating humidity		20% ~ 80% RH non-condensing
Connectivity		Energy efficiency		Energy Star 8.0 certified
Connectivity USB Type A x 7 (2.0 x 2 / 3.2 Gen 1 x 5), Type B x 3 (3.0), Type C x 2 (3.0) RS232 x 1 RJ45 (LAN) x 2 (Android / OPS) up to 1000Mbps Remote controller x 1 Built-in speaker 2 x 16 W / 1 x Subwoofer 16 W Dolby Audio Yes Array microphones x 8 Dimension (mm) Screen 1717.1 x 1065.3 x 121.3 mm Weight (kg) Net weight 55.5 Gross weight 70 Bezel width (mm) 16.6 / 16.6 / 16.6 / 16.6 Wall mounting (VESA) 800 x 400 (4 x M8 x 25L) (screw type / max. length) 800 x 400 (4 x M8 x 25L) Wall mount kit Included OPS slot Yes (supports single sign-on with Azure Active Directory and Google Workspace) Pen tray Yes	Connectivity	Input		
RS232		Output		
RJ45 (LAN)		USB		
Remote controller		RS232		x 1
Built-in speaker		,		x 2 (Android / OPS) up to 1000Mbps
Dolby Audio				
Array microphones	Audio	•		
Dimension (mm) Screen 1717.1 × 1065.3 × 121.3 mm		•		
Weight (kg)				
Mechanical Bezel width (mm) 16.6 / 16.6 / 16.6 / 16.6	Mechanical	Dimension (mm)		
Bezel width (mm) 16.6 / 16.6 / 16.6 / 16.6		- , -,		77.7
Mechanical Wall mounting (VESA) (screw type / max. length) Wall mount kit OPS slot NFC sensor Pen tray Wall mounting (VESA) (800 × 400 (4 × M8 × 25L) Included Yes Yes (supports single sign-on with Azure Active Directory and Google Workspace)				
(screw type / max. length) 800 × 400 (4 × M8 × 25L) Wall mount kit Included OPS slot Yes NFC sensor Yes (supports single sign-on with Azure Active Directory and Google Workspace) Pen tray Yes		1 7		16.6 / 16.6 / 16.6
OPS slot NFC sensor NFC sensor Pen tray Yes Yes (supports single sign-on with Azure Active Directory and Google Workspace) Yes		(screw type / max. length)		` '
NFC sensor Yes (supports single sign-on with Azure Active Directory and Google Workspace) Pen tray Yes				Included
Active Directory and Google Workspace) Pen tray Yes		OPS slot		Yes
·				
Warranty 3-year warranty on-site exchange				
	Warranty			3-year warranty on-site exchange

SOFTWARE



EZWrite 6

Open Microsoft documents and image files directly on the display, and save sessions in editable whiteboard files (IWB) with Cloud Whiteboarding.



InstaShare 2



X-Sign Broadcast

Announcement system for instant messaging and group notification. Send visual alerts, warnings, videos to all or one specific device.























NFC SENSOR & KEYPAD BUTTONS











CAMERA USB PORT, WIFI DONGLE & REMOTE CONTROLLER USB PORT



USB3.0 USB3.0

DOWN I/O



















SIDE I/O



















DIMENSIONS (MM)







Benq

